




Features

- 1000 μm x 1000 μm active area
- Low dark current
- Fast response time
- High speed epitaxy
- Fully depleted at 3.5 V

Description

High speed epitaxy PIN photodiode with 1.0 mm² square active area. Ceramic carrier type non hermetic SMD package with clear glass window (501127) or silicone potting (on request). Reflow solderable.

Application

- Pulsed light detection
- High speed photometry
- High speed optical communications
- Fiber optic light monitoring

RoHS


2002/95/EC




Absolute maximum ratings

Symbol	Parameter	Min	Max	Unit
T _{STG}	Storage temp	-40	100	°C
T _{OP}	Operating temp	-20	70	°C
V _{max}	Max reverse voltage		40	V
I _{PEAK}	Peak DC current		10	mA

Schematic



Spectral response (23 °C)



Electro-optical characteristics @ 23 °C

Symbol	Characteristic	Test Condition	Min	Typ	Max	Unit
	Active area		1000 x 1000			μm
	Active area		1.0			mm ²
I _D	Dark current	V _R = 3.5 V		0.01	0.1	nA
C	Capacitance	V _R = 0 V		20		pF
C	Capacitance	V _R = 3.5 V		8		pF
	Responsivity	λ = 635 nm		0.49		A/W
	Responsivity	λ = 800 nm		0.52		A/W
t _R	Rise time	V _R = 3.5 V; λ = 850 nm; R _L = 50 Ω		1.0		ns
V _{BR}	Breakdown voltage	I _R = 2 μA	40			V
	Shunt resistance	V _R = 10 mV		10000		M Ω
	N.E.P.	V _R = 3.5 V; λ = 850 nm		4 E-15		W/ $\sqrt{\text{Hz}}$

European, International Sales:






First Sensor AG
Peter-Behrens-Strasse 15
12459 Berlin
Germany
T +49 30 6399 2399
F +49 30 639923-752
sales.opto@first-sensor.com

USA:



First Sensor Inc.
5700 Corsa Avenue #105
Westlake Village
CA 91362 USA
T +1 818 706 3400
F +1 818 889 7053
sales.us@first-sensor.com

Quantum efficiency (23 °C)

Capacitance as fct of reverse bias (23 °C)

Dark current as fct of bias (23 °C)

Application hints:

Please refer to document "Instructions for handling and processing"

European, International Sales:


First Sensor AG
 Peter-Behrens-Strasse 15
 12459 Berlin
 Germany
 T +49 30 6399 2399
 F +49 30 639923-752
 sales.opto@first-sensor.com


USA:


First Sensor Inc.
 5700 Corsa Avenue #105
 Westlake Village
 CA 91362 USA
 T +1 818 706 3400
 F +1 818 889 7053
 sales.us@first-sensor.com

Technical Drawing, Package: LCC6.1

LCC6.1G with glass cover # 501127

LCC6.1S with silicone potting on request



European, International Sales:





First Sensor AG
Peter-Behrens-Strasse 15
12459 Berlin
Germany
T +49 30 6399 2399
F +49 30 639923-752
sales.opto@first-sensor.com

USA:



First Sensor Inc.
5700 Corsa Avenue #105
Westlake Village
CA 91362 USA
T +1 818 706 3400
F +1 818 889 7053
sales.us@first-sensor.com

Package dimension, large quantities on reel

Package dimension, small quantities in trays


Disclaimer: Due to our strive for continuous improvement, specifications are subject to change within our PCN policy according to JESD46C.

European, International Sales:


First Sensor AG
 Peter-Behrens-Strasse 15
 12459 Berlin
 Germany
 T +49 30 6399 2399
 F +49 30 639923-752
 sales.opto@first-sensor.com

USA:


First Sensor Inc.
 5700 Corsa Avenue #105
 Westlake Village
 CA 91362 USA
 T +1 818 706 3400
 F +1 818 889 7053
 sales.us@first-sensor.com